

FLECK® 2510

HIGH PERFORMANCE CONTROL VALVE



FEATURES/BENEFITS

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Continuous service flow rate of 19 GPM with a backwash of 17 GPM

Backwash capability accommodates softener tanks up to 16" and filter up to 16" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Time-tested, hydraulically-balanced piston for service and regeneration

Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

Filter or softener control valves

No hard water bypass piston

Brine cam auxiliary switch

Electromechanical timer auxiliary switch

Plumbing connections in 3/4" to 1-1/4" NPT, BSP, and sweat

Fiber-reinforced polymer or stainless steel bypass valve

Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration

Manual lever operations

SXT-Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems

XT- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programming as well as view of diagnostics

Electromechanical Timer- Simple to adjust and easy to service with quick access to all internal components



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to 979



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

Valve Material	Fiber-reinforced polymer
Inlet/Outlet	3/4", 1", or 1-1/4" NPT/ BSP/Sweat
Cycles	3 or 5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	19 GPM (4.3 m ³ /h)
Peak 25 psi drop	24 GPM (5.5 m ³ /h)
Cv flow at 1 psi drop	4.8
Max. Backwash 25 psi drop	17 GPM (3.9 m ³ /h)

REGENERATION

Downflow/Upflow	Downflow only
Adjustable Cycles	Yes
Time Available	
Electromechanical:	0 - 164 min/regeneration
SXT:	0 - 199 min/cycle
XT:	0 - 240 min/cycle

METER INFORMATION

Meter Accuracy	
3/4" Paddle/Turbine:	0.25 - 15 GPM ± 5% (0.06 - 3 m ³ /h)
Meter Capacity Range	
3/4" Standard:	125 - 2,125 gal (0.5 - 8 m ³)
3/4" Extended:	625 - 10,625 gal (2.5 - 40 m ³)
SXT:	1 - 999,900 gal (0 - 3,785 m ³)
XT:	1,000 - 9,900,000 gal (3.8 - 37,476 m ³)

DIMENSIONS

Distributor Pilot	1.05" O.D. (26.7 mm)
Drain Line	1/2" NPTF Quick-Connect
Brine Valve 1600:	3/8"
Injector System	1600
Mounting Base	2.5" – 8 NPSM
Height from Top of Tank	7.5" (191 mm)
Riser Tube Diameter	3/4" (19 mm)
Riser Height	1/4" Below top of tank

TYPICAL APPLICATIONS

Water Softener	6 - 16" diameter
Filters	8 - 16" diameter based on 10 GPM/ft ²

ADDITIONAL INFORMATION

Electrical Rating	24/110/220V 50/60 Hz
Estimated Shipping Weight	
Time Clock:	7 lbs
Metered Valve:	10 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

40729 REV C JL14 © 2013 Pentair Residential Filtration, LLC. All Rights Reserved.