

5600sxt SYSTEM **SPECIALS**

SYSTEM FEATURES and BENEFITS

- > Fiber-reinforced polymer valve body for superior Strength and durability. Non-Corrosive, and UV-resistant. Continuous service flow rate of 21gpm. And Meters Flow Rates Down To 1/4gpm
- > Controls Are User Friendly & Easy To Program
SXT-Large LCD display and user selectable Electronic Timer, Choice of Clock or Metered function: usable for filtration and softener Systems
- > Economical-Small Annual Power Consumption.
- > 5 Year Warranty On Control Valve.
- > 10 Year Warranty On Mineral Tank.
- > Can be ordered with you choice of plumbing adapters.
3/4 and 1" FNPT Stainless Steel Bypass, 3/4 and 1" Plastic NPT yokes and plastic bypass.
- > Brine tank can be ordered with safety & salt grid. (Optional)

RISER TWO TANK MODELS AVAILABLE

- > 56sxtR24 (24,000 Grain System, 8x44" Tank) 15x17" Brine Tank
- > 56sxtR32 (32,000 Grain System, 9x48" Tank) 15x17" Brine Tank
- > 56sxtR40 (40,000 Grain System, 10x44" Tank) 15x17" Brine Tank
- > 56sxtR48 (48,000 Grain System, 10x54" Tank) 18x33" Brine Tank
- > 56sxtR64 (64,000 Grain System, 12x52" Tank) 18x33" Brine Tank
- > 56sxtR80 (80,000 Grain System, 13x54" Tank) 18x40" Brine Tank



WE CAN CUSTOM DESIGN YOUR SYSTEMS TO MEET YOUR SPECIFIC NEEDS

CALL US AT 800-426-9375